



<b>EDGE 850: System Specifications</b>	
<b>Print Speed</b>	Up to 9.14 meters/min (30 ft/min)
<b>Technology</b>	Single Pass 4 Color LED (CMYK)
<b>Printer Processor<sup>1</sup></b>	533 MHz
<b>Media Width</b>	Minimum: 3.0 inches (76.2 mm) Maximum: 8.5 inches (216 mm)
<b>Print Width</b>	Minimum: 3.0 inches (76.2 mm) Maximum: 8.24 inches (209.3 mm)
<b>Print Length</b>	Up to 420 meters (1378 ft)
<b>Substrate Types<sup>2</sup></b>	Die Cut Label Stock Kiss Cut Label Stock Non Die Cut Label Stock Tag Stock
<b>Print Quality</b>	1200 x 600 dpi
<b>Toner Supplies<sup>3</sup></b>	CMY - 11,500 pages @ 5% K - 11,000 pages @ 5% (Rated according to ISO/IEC 19798 guidelines)
<b>Drum Supplies<sup>4</sup></b>	CMYK - 30,000 pages @ 5% (Rated according to ISO/IEC 19798 guidelines)
<b>Feeder System</b>	Input roll maximum outside diameter: 8 inches (203 mm) Core inside diameter: 3 inches (76.2 mm) Maximum input roll weight: 14 lbs (6.35 kg) Cut on the fly, auto cut Auto page width registration Front Panel LCD interface Web management system torque Auto adjusting form synchronization
<b>Rewinder System</b>	Output roll maximum diameter: 8 inches (203 mm) Core inside diameter: 3.0 inches (76.2 mm) Maximum output roll weight: 14 lbs (6.35 kg)
<b>Dimensions (H X W X D)</b>	Printer & Feeder: 26" x 17.1" x 21.5" (660 mm x 434 mm x 546 mm) Rewinder: 16" x 19.75" x 19" (406 mm x 502 mm x 483 mm)
<b>Weight</b>	Printer & Feeder: 110 lbs (49.9 kg) Rewinder: 27.65 lbs (12.54 kg)
<b>Operating Environment</b>	Temperature: 10°C to 20°C (50 to 89.6°F) Humidity: 20 to 60% RH
<b>Power</b>	110 - 127 VAC, 50/60 Hz @ 1150W 220 - 240 VAC, 50/60 Hz @ 1150W
<b>Certifications</b>	FCC Class A, CE, cTUVus, CCC
<b>Warranty</b>	1 year – Parts & Labour
<p>1. Published performance results based on laboratory testing. Individual results may vary.</p> <p>2. This product is designed and engineered to operate only with genuine iSys Label consumables and certified media substrates. Please contact iSys for the most current Certified Media List of substrates</p>	



available.

3. Letter-size sheets at 5% coverage. Printer ships with a 7,500 page set of starter toners.

4. Based on 500 cut-sheet pages/job.

iSys Label reserves the right to change product specifications without notice. Trademarks are the property of their respective manufacturers. ©2013 Copyright, iSys Label. All Rights Reserved. All content is subject to change without notice.

<b>EDGE 850: System Requirements</b>	
<b>CPU:</b>	Intel Xeon E5-1650 @ 3.20GHz, or Intel Core i7-3930K @ 3.20GHz
<b>RAM:</b>	12GB RAM (minimum)
<b>HDD:</b>	150GB SATA 10K or 15K RPM
<b>OS:</b>	Windows 7 Professional, or Ultimate 64-bit